## **CAN Adapter update**

Main Page > Frequently Asked Questions - FAQ > CAN Adapter update


The software of CAN adapters - <u>LV-CAN200</u>, <u>ALL-CAN300</u> and <u>CAN-CONTROL</u> can now be updated Over The Air by using <u>FOTA WEB</u> and one of the FMx1YX devices. Upgrading the software of the CAN adapter will add more program numbers, thus, more vehicle models will be supported.

**Please note**, that only the newer version of LV-CAN200 and ALL-CAN300 CAN adapters support this feature. The version of the CAN adapter can be checked by sending an SMS command <a href="https://linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/linear.com/lin

In order to update your device's firmware please follow a quick and simple step-by-step guide below. The procedure is the same for all devices.


- FMx1YX device, which is connected to the CAN adapter (or <u>FMB140</u> which has an internal CAN adapter), must be registered in FOTA WEB device's model, firmware version, serial number, and other information must be shown.
- Once a device connects to FOTA WEB on the next scheduled connection (or instant connection, initiated by an SMS command "web\_connect"), a small "CAN" logo will appear next to the device's IMEI number. And current version of the CAN adapter software can be checked in the table at the bottom of the page.





- In order to update the software of a CAN adapter, You should follow these steps:
  - 1. Select the devices by clicking the checkbox next to them
  - 2. Press "**Create task**" at the top-left corner of the page
  - 3. Select "**Update CAN adapter firmware**" task type
  - 4. Select the software date. We recommend selecting today's date, so the adapter would be


## updated to the newest possible software:



- Once the software update task has been assigned, it can be seen in the main window. Please note, that uploading will start after the next scheduled connection to FOTA WEB (or instant connection, initiated by an SMS command "web connect"):
- When the update is finished, a new software version can be seen in the details window after the next scheduled connection to FOTA WEB(or instant connection, initiated by an SMS command "web connect"):

## FMB150 Configuration Upload

- FMB150 CAN configuration can be uploaded Over The Air by using FOTA WEB.
- In order to download your vehicle's CAN configuration please follow a quick and simple stepby-step guide below. FMB150 device must be registered in FOTA WEB – the device's model, firmware version, serial number, and other information must be shown.
  - 1. Select the devices by clicking the checkbox next to them
  - 2. Press "Create task" at the top-left corner of the page
  - 3. Select "Upload CAN configuration" task type
  - 4. Select Vehicle Make, and Model:



- Once the CAN configuration upload task has been assigned, it can be seen in the main window. Please note, that uploading will start after the next scheduled connection to FOTA WEB (or instant connection, initiated by an SMS command "web connect"):
- When the update is finished, a new software version can be seen in the details window after the next scheduled connection to FOTA WEB(or instant connection, initiated by an SMS command "web\_connect").

## FMB150 CAN adapter update

FMB150 CAN chip update can be done through FOTA Web by creating a task called "Update FMX150 CAN Chip". Select the FMB150 device that you would like the CAN chip to be updated and press "Create task". In the create task window select FM CAN Chip FW and press "Create". To initiate the task immediately you can send the "web\_connect" command or perform a hard reset of the device. Below is a visual representation of the steps described above.

