## FMM80A

PLUG AND PLAY TRACKER DESIGNED FOR NORTH AMERICA



FMx8 series devices are EASY to use and FAST to install. The number "8" brings everything together in one place and stands out with its simplicity of basic tracking.

Teltonika FMM80A tracker is a small OBDII Plug and Play device with 4G LTE Cat M1 and Bluetooth connectivity. An extremely fast and easy installation allows connecting device in a few seconds! No tools or engineers are required for installation.

Thanks to that, FMM80A tracker perfectly suits for light vehicle tracking in applications like courier delivery service, car rental & leasing, insurance telematics and many other industries, where simple integration is a must. It is a perfect solution for real time monitoring, specially for beginners and those, who are looking for new opportunities to expand their businesses.

FMM80A device has a built-in accelerometer, which provides accurate crash trace data. This tracker also supports various Bluetooth Low Energy sensors, beacons, firmware and configuration update via Bluetooth. All of that increase the number of possible use scenarios in any market. It is quick to install, easy to use and ready to start tracking in minutes!





Product	
Model name	FMM80A-Q2IB0
Module	
Name	Quectel BG95-M1 with Teltonika TM2500
Technology	LTE CAT M1/GNSS/BLUETOOTH
GNSS	
GNSS	L1: GPS, GLONASS, GALILEO, BEIDOU, SBAS*, QZSS*, DGPS*, AGPS
Receiver	33 channel
Tracking sensitivity	-165 dBM
Position Accuracy	< 2.5 m CEP
Velocity Accuracy	< 0.1 m/s (within +/- 15% error)
Hot start	< 1 s
Warm start	< 25 s
Cold start	< 35 s

\*Optional modes available with custom firmware applications, for more information contact your sales manager.

Cellular	
4G bands	LTE FDD (CAT M1): B1/B2/B3/B4/B5/B8/B12/B13/B18/B19/B20/B25/B26/B27/B28/B66/B85
Data transfer	LTE FDD (CAT M1): Max. 588 Kbps (DL) / Max. 1119 Kbps (UL)
Data support	SMS (TEXT, PDU), Network protocols (TCP,UDP,TLS,EGTS,MQTT)
Power	
Input voltage range	10 - 30 V DC with overvoltage protection
Internal Back-up battery	115 mAh Li-Ion, 3.7 V battery (0.43 Wh)
Internal fuse	3 A, 125 V
Bluetooth	
Specification	4.0 + LE
Supported peripherals	Temperature and Humidity sensor, Inateck Barcode Scanner, Universal BLE sensors support

## **TELTONIKA** | Telematics

## Physical specification

Physical specification	
Dimensions	67,2 x 49,6 x 25 mm (L x W x H)
Weight	63 g
Operating environment	
Operating temperature (without battery)	-40 °C to +85°C
Storage temperature (without battery)	-40 °C to +85 °C
Operating temperature (with battery)	0 °C to +40 °C
Sotrage temperature (with battery)	-20 °C to +60 °C
Operating humidity	5% to 95% non-condensing
Ingress Protection Rating	IP41
Battery charge temperature	0 °C to +45 °C
Battery discharge temperature	-20 °C to +60 °C
Battery storage temperature	-20 °C to +45 °C for 1 month
suttery storage temperature	-20 °C to +35 °C for 6 months
nterface	
Connection	OBDII socket
GNSS antenna	Internal High Gain
GSM antenna	Internal High Gain
JSB	2.0 USB Micro B
ED indication	2 status LED lights
SIM	Micro-SIM
Memory	128MB internal flash memory
Features	
Sensors	Accelerometer
icenarios	Green Driving, Over Speeding detection, Jamming detection, GNSS Fuel Counter, Excessive Idling detection, Unplug detection, Towing detection, Crash detection, Auto Geofence, Manual Geofence, Trip
ileep modes	GPS Sleep, Online Deep Sleep, Deep Sleep, Ultra Deep Sleep
Configuration and firmware update	FOTA Web, Teltonika Configurator (USB, Bluetooth)
SMS	Configuration, Events, Debug
GPRS commands	Configuration, Debug
Fime Synchronization	GNSS, NITZ, NTP

## Certification & Approvals \*

Regulatory

AT&T, IC, FCC, PTCRB

\* in progress