

FMB001 GSM Operators settings

[Main Page](#) > [OBd Trackers](#) > [FMB001](#) > [FMB001 Configuration](#) > **FMB001 GSM Operators settings**

GSM settings

Operator lists

FMB001 can work in different modes (use different settings) according to the operator list defined. Operator list is used for Data Acquisition mode switching (see [Data acquisition settings](#) section for more details). Modes are changed based on the GSM operator FMB001 is connected to.

The screenshot displays the 'GSM Settings' configuration page. On the left is a vertical sidebar menu with the following items: Security, System, GPRS, Data Acquisition, SMS \ Call Settings, GSM Operators (highlighted), Features, Accelerometer Features, Auto Geofence, Manual Geofence, Trip \ Odometer, Bluetooth, Bluetooth 4.0, Beacon List, 1-Wire, I/O, OBD II, CAN Adapter, and RS232 \ RS485. The main content area is titled 'GSM Settings' and is divided into two sections: 'Roaming Operator List' and 'Operator Black List'. Each section contains a table with 20 rows, numbered 1 to 20. Each row has a dropdown menu next to the number. Below each table are 'Import CSV' and 'Export CSV' buttons. The interface is blue-themed with a footer containing social media icons and a gear icon.

Configuring device roaming and blacklist operators is recommended to optimize device performance by mitigating additional latency.

If the roaming operator list is left empty, FMB001 will automatically detect the home operator. If the home operator is written to the roaming operator list, it will still be detected as a home operator. Any operator not in the roaming operator list (except the home operator) will be recognized as an unknown operator and FMB001 will work in Unknown mode (make sure it is configured to allow data sending - GPRS context is enabled).

If the user wants FMB001 to not connect and work with a particular operator it has to be written to *Operator Blacklist*. Up to 50 operators may be entered into this list.

The Operator search procedure is initiated every 15 minutes. During the search, FMB001 tries to connect to the operator providing the strongest signal. It will prioritize operators that are specified in the operator list. If no operators from the operator list are available, the device will try to connect to an operator from the blacklist. If the device connects to an operator from the blacklist, the best operator search procedure is initiated instantly. During the time when the device is connected to a

blacklisted operator, no GPRS connection would be initiated and no data would be sent via GPRS. However, the ability to send SMS commands to the device would remain. If no suitable operator is found on both lists, the device will try to connect to a remaining available operator with the strongest signal.