

# FMC800 General description

[Main Page](#) > [Fast & Easy Trackers](#) > [FMC800](#) > [FMC800 Manual](#) > **FMC800 General description**

FMC800 is a tracking terminal with GNSS and LTE/GSM connectivity, which is able to collect device coordinates and transfer them via LTE/GSM networks to a server. FMC800 is a LTE CAT 1 device. The main feature of FMC800 is it's easy installation via OBD port. It is a perfect tracker for a wide range of use cases - including fleet management of light commercial vehicles, driver log-book, insurance telematics (UBI), car rental & leasing and more.

□

## Contents

- [1 Package contents](#)
- [2 Basic characteristics](#)
- [3 Technical features](#)
- [4 Technical information about internal battery](#)
- [5 Electrical characteristics](#)
- [6 Absolute maximum ratings](#)

## Package contents

The FMC800 device is supplied to the customer in a cardboard box containing all the equipment that is necessary for operation. The package contains:

- FMC800 device;
- Top and bottom device cover parts;
- OBD II power supply adapter.

## Basic characteristics

GSM / GPRS / GNSS features:

- FMC800-QJIB0: Quectel EG915U-EU with Teltonika TM2500;
- Technology LTE CAT 1/GSM/GPRS/GNSS/BLUETOOTH;
- SMS (text, data);
- Integrated GNSS receiver;
- Up to -165 dBm GNSS receiver sensitivity.

CELLULAR:

Technology	Supported bands
2G bands	FMC800-QJIB0: GSM: B2/B3/B5/B8 850/900/1800/1900
4G bands	FMC800-QJIB0: LTE FDD: B1/B3/B7/B8/B20/B28
Data transfer (Quectel)	LTE: LTE FDD: Max 10Mbps (DL)/Max 5Mbps (UL) GSM: GPRS: Max 85.6Kbps (DL)/Max 85.6Kbps (UL)

## Hardware features:

- Built-in movement sensor;
- Built-in Bluetooth 3.0;
- Built-in Bluetooth 4.0;
- Internal High Gain GNSS antenna;
- Internal High Gain GSM antenna;
- 128 MB Flash (422 400 Records);
- 170 mAh Li-ion rechargeable 3.7 V battery.

## Interface features:

- Power supply: +10...+30 V;
- USB port;
- OBD II;
- 2 LEDs indicating device status.

## Technical features

<b>Part name</b>	<b>Physical specification</b>
Navigation indication	LED
Modem indication	LED
OBD-II	Standard OBD-II connector
USB	Micro USB socket

### Technical details

2 W max.	GPRS: max 50 mA
Current consumption at 12 V	Nominal: average 35 mA
	GPS sleep: average 12 mA
	Deep Sleep: average 4.5 mA
Battery charge current	Average: 140 mA
	Rated: 250 mA
Operating temperature (without battery)	-40 ... +85 °C
Storage temperature (without battery)	-40 ... +85 °C
Storage relative humidity	5 ... 95% (no condensation)
Internal fuse	3 A, 125 V
Device + case + battery weight	63 g

## Dimension drawing:



## Technical information about internal battery

Internal back-up battery	Battery voltage (V)	Nominal capacity (mAh)	Power (Wh)	Charge temperature (°C)	Discharge temperature (°C)	Storage temperature (°C)
Li-ion rechargeable battery	3.75□3.90	170	0.64 - 0.66	0 to +45	-20 to +60	-20 to +45 for 1 month -20 to +35 for 6 months

Batteries are covered by 6 month [warranty](#) support.

- ✘ CAUTION: RISK OF EXPLOSION IF BATTERY IS REPLACED BY AN INCORRECT TYPE. DISPOSE OF USED BATTERIES ACCORDING TO THE INSTRUCTIONS.

Battery should not be disposed of into general household waste.

- ✘ Bring damaged or worn-out batteries to your local recycling center or dispose them into a battery recycle bin commonly found in supermarkets.

## Electrical characteristics

Characteristic description	Value			Unit
	Min.	Typ.	Max.	
Supply Voltage:				
Supply Voltage (Recommended Operating Conditions)	+10		+30	V
Input voltage (Recommended Operating Conditions)	0		Supply voltage	V

## Absolute maximum ratings

Characteristic description	Value			Unit
	Min.	Typ.	Max.	
Supply Voltage (Absolute Maximum Ratings)	-32		+32	V