

# FMM640 General description

[Main Page](#) > [EOL Products](#) > [FMM640](#) > [FMM640 Manual](#) > **FMM640 General description**

Teltonika FMM640 is PROFESSIONAL worldwide tracker with GNSS, LTE CAT M1, NB IoT connectivity, additional GSM backwards compatibility that makes this device usable with newest and most cost efficient technologies. FMM640 features like FMS CAN data (J1939), fuel CAN data (J1708), tachograph live data (K-line), remote tachograph file download, various third party RS232 or RS485 devices support and Dual-SIM will maximize your fleet efficiency. Device supports universal BLE sensors, beacon tags. Terminal is suitable for applications like international logistics, refrigerated transport, agriculture, construction & mining, security & emergency services and even more.

□

## Contents

- [1 Package contents](#)
- [2 Basic characteristics](#)
- [3 Technical features](#)
- [4 Technical information about internal battery](#)
- [5 Battery tests](#)
- [6 Electrical characteristics](#)
- [7 Absolute maximum ratings](#)

## Package contents

Usually the FMM640 device sample is supplied to the customer in a cardboard box containing all the equipment that is necessary for operation. The package contains:

- FMM640 device;
- 4 screws for assembling device
- GPS/GLONASS antenna
- GSM antenna
- USB cable
- Port 1/2 cable
- Port 3 cable
- Ni-MH Rechargeable battery, 8.4V, 550 mA.
- Input and output power supply cable with 2x10 connection pins.

## Basic characteristics

Cellular:

- LTE CAT M1/CAT NB1/EGPRS technologies
- 2G bands: Quad-band 800/850/900/1900 MHz
- 4G bands:

- FDD-LTE: B1/ B2/ B3/ B4/ B5/ B8/ B12/ B13/ B18/B19/ B20/ B28
- TDD-LTE: B39 (for Cat.M1 only)
- Data transfer:
  - LTE FDD: Max. 375Kbps (DL)/Max.375Kbps (UL)
  - LTE TDD: Max. 32Kbps (DL)/Max. 70Kbps (UL)
  - GPRS: Max. 107Kbps (DL)/Max. 85.6Kbps (UL)
- SMS (text, data)

#### GNSS features:

- Tracking: 33/ 99 acquisition channels
- -165 dBm sensitivity
- Hot start <1s
- Warm Start < 25s
- Cold start < 35s
- NMEA-183 protocol
- GPS, GLONASS, GALILEO, BEIDOU, SBAS, QZSS, DGPS, AGPS
- Accuracy < 3m

#### Hardware features:

- STM32 processor;
- 2 MB internal Flash memory;
- External memory card slot;
- Built-in accelerometer;
- Built-in Blue-tooth 5.0;
- Internal backup battery included;

#### Interface:

- Integrated KLINE
- Dual CAN J1939
- J1708 CAN
- RS485 and 2x RS232 support
- 4 Digital Inputs for object status monitoring
- 4 Digital Open-collector Outputs (controlling external relays, LED, buzzers, etc.)
- 4 Analog Inputs
- 1-wire interface
- Ni-Mh 550 mAh internal battery
- MicroSD card
- 2 status LED
- Dimensions: L(104,1mm)xW(76,8mm)xH(31,5mm)
- Configuration and firmware update (via FOTA and USB cable)
- External GSM antenna for higher sensitivity
- External GNSS antenna for higher sensitivity

#### Special features:

- Fast position fix;
- High Quality track even in high density urban canyon;
- Ultra small case;
- Ready for harsh environment;

- Easy to mount in limited access areas;
- Firmly fasten;
- 2 LED status indication;
- Real time tracking;
- Smart data acquisition based on:
  - Time;
  - Speed;
  - Angle;
  - Distance;
  - Ignition or any other I/O event;
- Sending acquired data via GPRS;
- GPRS and SMS I/O events;
- Virtual odometer;
- Jamming detection;
- Configurable using Secured SMS Commands;
- 1x micro SIM card; 1x eSIM;
- Overvoltage protection;
- Reverse polarity protection;

| <b>Description</b>                    | <b>Voltage</b> | <b>Duration</b> |
|---------------------------------------|----------------|-----------------|
| Normal operation                      | +10 ... +30 V  | Unlimited       |
| Protection turns on, device turns off | 34 V           | Unlimited       |
| Maximum voltage                       | < 70 V         | Unlimited       |
| Maximum voltage impulse               | 90 V           | 5 ms            |

## Technical features

| <b>Part name</b>      | <b>Physical specification</b> |
|-----------------------|-------------------------------|
| Navigation indication | LED                           |
| Modem indication      | LED                           |
| Socket                | Soldered inner socket         |
| USB                   | Mini USB socket               |
| GNSS                  | External GNSS antenna         |
| GSM                   | External GSM antenna          |

### Technical details

|   |   |
|---|---|
| 2 W max.<br>Current consumption at 12 V | GPRS: average 60 mA<br>rms<br>Nominal: average 40 rms<br>GNSS sleep: average 31<br>mA<br>Deep Sleep: average 4<br>mA<br>Online Deep Sleep:<br>average 13 mA |
| 2 W max.<br>Current consumption at 24 V | GPRS: average 32 mA<br>Nominal: average 22 mA<br>GNSS sleep: average 16<br>mA<br>Deep Sleep: average 2,6<br>mA<br>Online Deep Sleep:<br>average 6,7 mA      |
| Battery charge current                  | Average 55 mA   |
| Operating temperature (without battery) | -40..+85  |
| Storage temperature (without battery)   | -40..+85  |
| Storage relative humidity               | 5..95% (no condensation)  |
| Device + case + battery weight          | 200 g   |

Dimension drawing:



## Technical information about internal battery

| Internal back-up battery   | Battery voltage (V) | Nominal Capacity (mAh) | Charging temperature (°C) |
|----------------------------|---------------------|------------------------|---------------------------|
| Ni-MH rechargeable battery | 8.4□10.0            | 550                    | 0 - 45                    |

Batteries are covered by 6 month [warranty](#) support.

CAUTION: RISK OF EXPLOSION IF BATTERY IS REPLACED BY AN INCORRECT TYPE. DISPOSE OF USED BATTERIES ACCORDING TO THE INSTRUCTIONS.

Battery should not be disposed of into general household waste.

Bring damaged or worn-out batteries to your local recycling center or dispose them into a battery recycle bin commonly found in supermarkets.

## Battery tests

The amount of time the device will work from internal battery depends on the battery health, how often the device saves/sends information to the server, external peripherals connected to the device and the results may also differ depending on firmware used.

For general comparison purpose, and to see what results can be achieved, you can refer to the

following internal test results in different modes and sending frequencies:

| <b>Mode:</b>      | <b>Min Period (data saving frequency)</b> | <b>Send Period (data sending frequency)</b> | <b>Starting Voltage</b> | <b>Cut off Voltage</b> | <b>Time achieved</b>          |
|-------------------|---|---|-------------------------|------------------------|-------------------------------|
| Operating         | 10 seconds                                | 60 seconds                                  | 10,1V                   | 7,6V                   | 438 min (7 hours 18 minutes)  |
| Operating         | 60 seconds                                | 60 seconds                                  | 10,5V                   | 7,6V                   | 506 min (8 hours 26 minutes)  |
| Deep Sleep        | 12 hours                                  | 12 hours                                    | 10,2V                   | 8,2V                   | 5040 min (84 hours 0 minutes) |
| Online Deep Sleep | 12 hours                                  | 12 hours                                    | 10,1V                   | 8,0V                   | 2160 min (36 hours 0 minutes) |

## Electrical characteristics

| <b>Characteristic description</b>                                   | <b>Value</b> |             |                | <b>Unit</b> |
|---|--------------|-------------|----------------|-------------|
|   | <b>Min.</b>  | <b>Typ.</b> | <b>Max.</b>    |             |
| Supply Voltage:   |              |             |                |             |
| Supply Voltage (Recommended Operating Conditions)                   | +10          |             | +30            | V           |
| Digital Output (Open Drain grade):                                  |              |             |                |             |
| Drain current (Digital Output OFF)                                  |              |             | 120            | µA          |
| Drain current (Digital Output ON, Recommended Operating Conditions) |              |             | 0.5            | A           |
| Static Drain-Source resistance (Digital Output ON)                  |              | 400         | 300            | mΩ          |
| Digital Input:  |              |             |                |             |
| Input resistance (DIN1)   | 15           |             |                | kΩ          |
| Input resistance (DIN2)   | 15           |             |                | kΩ          |
| Input resistance (DIN3)   | 15           |             |                | kΩ          |
| Input voltage (Recommended Operating Conditions)                    | 0            |             | Supply voltage | V           |
| Input Voltage threshold (DIN1)                                      |              | 7.5         |                | V           |
| Input Voltage threshold (DIN2, DIN3, DIN4)                          |              | 2.5         |                | V           |
| Analog Input:   |              |             |                |             |
| Input voltage (Recommended Operating Conditions), Range 1           | 0            |             | +10            | V           |
| Input resistance, Range 1   |              | 120         |                | kΩ          |
| Input voltage (Recommended Operating Conditions), Range 2           | 0            |             | +30            | V           |
| Input resistance, Range 2   |              | 147         |                | kΩ          |

### Output Supply Voltage 1-Wire:

|   |      |      |          |
|---|------|------|----------|
| Supply voltage                          | +4.5 | +4.7 | V        |
| Output inner resistance                 | 7    |      | $\Omega$ |
| Output current ( $U_{out} > 3.0$ V)     | 30   |      | mA       |
| Short circuit current ( $U_{out} = 0$ ) | 75   |      | mA       |

### CAN Interface:

|                                     |     |     |          |            |
|-------------------------------------|-----|-----|----------|------------|
| Internal terminal resistors CAN bus | 120 |     | $\Omega$ |            |
| Differential input resistance       | 19  | 30  | 52       | k $\Omega$ |
| Recessive output voltage            | 2   | 2.5 | 3        | V          |
| Differential input resistance       | 0.5 | 0.7 | 0.9      | V          |
| Common mode input voltage           | -30 |     | 30       | V          |

### Power supply current (Hardware version with internal battery):

|   |     |     |    |
|---|-----|-----|----|
| Deep Sleep, average, $I_{cc.ds}$  | 2.5 | 4   | mA |
| Sleep, average, $I_{cc.ds}$ , $V_{cc}=10$ V   | 45  |     | mA |
| Sleep, average, $I_{cc.ds}$ , $V_{cc}=30$ V   | 25  |     | mA |
| $U_{cc}=12.6$ V, all modules fully working, internal battery is charging, $I_{cc1}$ |     | 350 | mA |
| $U_{cc}=12.6$ V, all modules fully working, internal battery is charging, $I_{cc2}$ |     | 300 | mA |
| $U_{cc}=25.2$ V, all modules fully working, internal battery is charging, $I_{cc3}$ |     | 195 | mA |
| $U_{cc}=25.2$ V, all modules fully working, internal battery is charging, $I_{cc4}$ |     | 140 | mA |

### RS232/RS485 Input Voltage:

|   |     |     |   |
|---|-----|-----|---|
| RS485 input voltage range on A or B pin (common-mode voltage) | -7  | +12 | V |
| RS232 input voltage range (common-mode voltage)               | -15 | +15 | V |

**✘ Analog Input error margin can increase if temperature varies.**

## Absolute maximum ratings

| Characteristic description  | Value |      |           |
|---|-------|------|-----------|
|   | Min.  | Typ. | Max. Unit |
| Supply Voltage<br>(Absolute Maximum Ratings)  | -32   | +32  | V         |
| Drain-Source clamp threshold voltage<br>(Absolute Maximum Ratings), ( $I_{drain} = 2$ mA) |       | +36  | V         |
| Digital Input Voltage<br>(Absolute Maximum Ratings)                                       | -32   | +32  | V         |
| Analog Input Voltage<br>(Absolute Maximum Ratings)  | -32   | +32  | V         |
| RS232 Input Voltage<br>(Absolute Maximum Ratings)   | -25   | +25  | V         |