

[https://wiki.teltonika-gps.com/view/February\\_22\\_Change\\_Log](https://wiki.teltonika-gps.com/view/February_22_Change_Log)

# February 22 Change Log

[Teltonika wiki change log](#) > **February 22 Change Log**

## GENERAL INFORMATION

1. Updated iBeacon/iSensor protocol description:

[https://wiki.teltonika-gps.com/view/EYE\\_BEACON\\_/BTSID1#EYE\\_Beacon\\_Protocol\\_overview](https://wiki.teltonika-gps.com/view/EYE_BEACON_/BTSID1#EYE_Beacon_Protocol_overview)

[https://wiki.teltonika-gps.com/view/EYE\\_SENSOR\\_/BTSMP1#EYE\\_Sensor\\_Protocol\\_overview](https://wiki.teltonika-gps.com/view/EYE_SENSOR_/BTSMP1#EYE_Sensor_Protocol_overview)

## AVL/PARAMETER ID UPDATES

2. FM64 AVL ID page was updated. AVL ID 48 description was modified:

[https://wiki.teltonika-gps.com/view/FMB640\\_Teltonika\\_Data\\_Sending\\_Parameters\\_ID](https://wiki.teltonika-gps.com/view/FMB640_Teltonika_Data_Sending_Parameters_ID)

## CREATED PAGES

3. Page „*How to capture ELA Beacon internal battery voltage?*“ created and added to FAQ list:

[https://wiki.teltonika-gps.com/view/How\\_to\\_capture\\_ELA\\_Beacon\\_internal\\_battery\\_voltage%3F](https://wiki.teltonika-gps.com/view/How_to_capture_ELA_Beacon_internal_battery_voltage%3F)