

TSM232

[Main Page](#) > [Accessories](#) > TSM232



This Product is started transition to EOL and will be discontinued by 2022.01.01:

- **Last Order date: 2021.10.01**
- **End Of Production date: 2022.01.01**
- **End of Bug-Fixing date: 2023.07.01**
- **End Of Support date: 2024.01.01**

Teltonika TSM232 is the Iridium SATELLITE terminal with a backup battery. The full solution combines Teltonika TSM232 with Teltonika FM63XY, FMB630, or FMB640 connected via RS232. This solution allows transferring data to a server via the Iridium satellite network when other terrestrial networks are unavailable. High capacity internal Ni-MH battery ensures long autonomous working hours when the main power source is disconnected. Such a solution meets the demand for high-security logistics, marine transport, construction & mining transport, oil/gas industry, public safety, government/defense, and more.



Contents

- [1 Basic characteristics](#)
- [2 Technical Information about internal battery](#)
- [3 Technical characteristics](#)
- [4 TSM232 Current consumption from battery](#)
- [5 Certification & Approvals](#)
- [6 FAQ](#)
- [7 YouTube](#)
- [8 Product Change Notifications](#)
 - [8.1 2020.06.29: TSM232 END OF LIFE Announcement](#)
 - [8.2 2019.12.13: Top Sticker/Tampography Changes](#)
 - [8.3 2019.07.10: new eco friendly box](#)
- [9 External Links](#)

Basic characteristics

Features:

- Data transferring via Iridium satellite network when GSM network is unavailable
- Smart RS232 communication algorithm
- One FM63XY/FMB630/FMB640 message size forwarded to TSM232 is only 14bytes
- Message contains: Time/Coordinates/Speed/DIN1-4/DOUT1-2/Event ID
- Data sending can be initiated by periodic time interval or by panic priority event Specification:
- Iridium satellite transceiver 9603

- CPU STM32F103VDH6

Interface:

- RS232
- External Iridium antenna
- Internal Ni-MH backup rechargeable battery 7.2V 400mAh
- External power input DC 10-30V
- USB
- Digital input
- Analog input
- Digital output

Technical Information about internal battery

Internal backup battery	Battery voltage (V)	Nominal capacity (mAh)	Power(Wh)(mAh)	Charging temperature (°C)	Standard discharge temperature (°C)
Ni-MH Prismatic Battery pack	7,2 □ 7,5	400	2,95 - 3,07	Ambient Temperature: 20±5	Ambient Temperature: 20±5

CAUTION: RISK OF EXPLOSION IF BATTERY IS REPLACED BY AN INCORRECT TYPE. DISPOSE OF USED BATTERIES ACCORDING TO THE INSTRUCTIONS.

Battery should not be disposed of into general household waste.

Bring damaged or worn-out batteries to your local recycling center or dispose them into a battery recycle bin commonly found in supermarkets.

Technical characteristics

PARAMETER	VALUE			Unit
	Mini mum	Typic al	Maxi mum	
Supply Voltage				
Supply Voltage (Recommended Operating Conditions)	+10		+30	V
Digital Output (Open Drain grade)				
Drain current (Digital Output OFF)			120	µA

Drain current (Digital Output ON, Recommended Operating Conditions)	500	mA
--	-----	----

Static Drain- Source resistance (Digital Output ON)	120	mΩ
--	-----	----

Digital Input

Input resistance (DIN1)	59,9	kΩ
------------------------------------	------	----

Input Voltage (Recommended Operating Conditions)	0	60	V
---	---	----	---

Input Voltage threshold (DIN1)	7,5	7,7	8	V
---	-----	-----	---	---

Analog Input

Input Voltage (Recommended Operating Conditions), Range1	0	10	V
---	---	----	---

Input resistance, Range1	120	kΩ
-------------------------------------	-----	----

Additional specifications:

- Input current/power specification - 1 A Max.
- Use 3A, 125V external fuse.
- Internal fuse specifications: Quick-acting; Rated current: 3A; Rated Breaking Capacity: 50A @ AC/DC 125V.
- The device uses SELV limited power source. The nominal voltage is 12 V DC. The allowed range of voltage is 10 V...30 V DC.

TSM232 Current consumption from battery

Mode/Voltage battery	12 V	7.2 V
Disconnected RS232	23.575	37.736
Connected RS232 (0 min send) with SIM (sleep)	8.246	14.994
Connected RS232 (1 min send)	19.808	30.473

Certification & Approvals

- [TSM232 CE / RED](#)

FAQ

- [TSM232 and FMB6](#)

YouTube

- [Teltonika TSM232 and FMB630 quick start guide](#)

Product Change Notifications

2020.06.29: TSM232 END OF LIFE Announcement



The product End of Life (EOL) announcement signifies that a product has entered the final phase of Teltonika Product Life Cycle. Announcement serves as an advance notice of product termination in accordance with Teltonika EOL policy. Nevertheless, there is still enough time for you to order and get support that you need for the products that will be discontinued. Please contact your sales manager for more information.

EOL Plan:

- **Last Order date: 2021.10.01**
- **End Of Production date: 2022.01.01**
- **End of Bug-Fixing date: 2023.07.01**
- **End Of Support date: 2024.01.01**

2019.12.13: Top Sticker/Tampography Changes

We would like to inform you, that sticker changed to tampography of TSM232 Satellite terminals and was updated in the factory on the 13th of December.

Change description		
Change type	External/visual	
Detailed description	Top Sticker/Tampography design changed	
Change reasons	Old Sticker Version: 	New Tampography Version: 
Product release date	Updated tampography will be used from the time when the stock will be sold all leftovers.	
Affected products		
Model	Affected order codes	Order code changes
TSM232	TSM232*****	No changes
Change impact		
Risk assessment	No risk factors encountered with this change	
Suggested implementation plan	No implementation plan needed	
Acknowledgement of PCN receipt		
If no feedback is received within two weeks after the issue date of this notification - Teltonika may accept that this change has been tacitly accepted and can implement the change as indicated above		

To download the pdf version of this notification, [click here](#).

2019.07.10: new eco friendly box

Effective July 2019 week 28, TSM232 Satellite terminals will be packed with a **new eco-friendly**

box.

Change description

Change type	Packaging
Detailed description	Improved and more environmentally friendly packaging box
Change reasons	The new box is better for the environment
Product release date	July 2019, week 28

New version:



External Links

<https://teltonika-gps.com/product/tsm232>