

Template:FMC125 manual supported frequency bands table

Product code	Region (operator)	Module name	Supported bands
FMC125 TL****	EU, MEA	<ul style="list-style-type: none">• MeiG SLM320-PE2C (jamming detection), TM2500	<ul style="list-style-type: none">• 4G (LTE-FDD): B1 (2100 MHz), B3 (1800 MHz), B7 (2600 MHz), B8 (900 MHz), B20 (800 MHz), B28 (700 MHz)• 4G (LTE-TDD): B38 (2600 MHz), B40 (2300 MHz), B41 (2500 MHz)• 2G: B2 (1900 MHz), B3 (1800 MHz), B5 (850 MHz), B8 (900 MHz)
FMC125 47****	APAC, LATAM	<ul style="list-style-type: none">• MeiG SLM320-L16A (jamming detection), TM2500	<ul style="list-style-type: none">• 4G (LTE-FDD): B1 (2100 MHz), B2 (1900 MHz), B3 (1800 MHz), B4 (1700 MHz), B5 (850 MHz), B7 (2600 MHz), B8 (900 MHz), B20 (800 MHz), B28 (700 MHz)• 4G (LTE-TDD): B40 (2300 MHz)• 2G: B3 (1800 MHz), B8 (900 MHz)