

Template:FMC13A Electrical characteristics

Electrical characteristics

Characteristic description	Value		
	Min.	Typ.	Max. Unit
Supply Voltage:			
Supply Voltage (Recommended Operating Conditions)	+10		+30 V
Digital Output (Open Drain grade):			
Drain current (Digital Output OFF)			120 μ A
Drain current (Digital Output ON, Recommended Operating 0.1 Conditions)			0.5 A
Static Drain-Source resistance (Digital Output ON)		400	600 m Ω
Digital Input:			
Input resistance (DIN1)	47		k Ω
Input resistance (DIN2)	38.45		k Ω
Input resistance (DIN3)	150		k Ω
Input voltage (Recommended Operating Conditions)	0		Supply voltage
Input Voltage threshold (DIN1)		7.5	V
Input Voltage threshold (DIN2)		2.5	V
Input Voltage threshold (DIN3)		2.5	V
Analog Input:			
Input voltage (Recommended Operating Conditions), Range 1	0		+10 V
Input resistance, Range 1		38.45	k Ω
Measurement error on 12V, Range 1		0.9	%
Additional error on 12 V, Range 1		108	mV
Measurement error on 30 V, Range 1		0.33	%
Additional error on 30 V, Range 1		88	mV
Input Voltage (Recommended Operating Conditions), Range 2	0		+30 V
Input resistance, Range 2		150	k Ω
Measurement error on 12V, Range 2		0.9	%
Additional error on 12 V, Range 2		108	mV

Measurement error on 30 V, Range 2		0.33		%
Additional error on 30 V, Range 2		88		mV
Output Supply Voltage 1-Wire:				
Supply voltage		+4.5	+4.7	V
Output inner resistance		7		Ω
Output current ($U_{out} > 3.0$ V)		30		mA
Short circuit current ($U_{out} = 0$)		75		mA
Ground sense:				
Input resistance	38.45			k Ω
Input voltage (Recommended operating conditions)	0		Supply voltage	V
Input voltage threshold		0.5		V
Sink current		180		nA

CAN interface:

Internal terminal resistor CAN bus (no internal termination resistor)	-	-	-	Ω
Differential input resistance	19	30	52	k Ω
Recessive output voltage	2	2.5	3	V
Differential receiver threshold Voltage	0.5	0.7	0.9	V
Common mode input voltage	-30	-	30	V

✘ Analog Input error margin can increase if temperature varies.