

Template:FMM640 Electrical characteristics

Electrical characteristics

Characteristic description	Value			Unit
	Min.	Typ.	Max.	
Supply Voltage:				
Supply Voltage (Recommended Operating Conditions)	+10		+30	V
Digital Output (Open Drain grade):				
Drain current (Digital Output OFF)			120	µA
Drain current (Digital Output ON, Recommended Operating Conditions)			0.3	A
Static Drain-Source resistance (Digital Output ON)		400	300	mΩ
Digital Input:				
Input resistance (DIN1)	15			kΩ
Input resistance (DIN2)	15			kΩ
Input resistance (DIN3)	15			kΩ
Input voltage (Recommended Operating Conditions)	0		Supply voltage	V
Input Voltage threshold (DIN1)		7.5		V
Input Voltage threshold (DIN2, DIN3, DIN4)		2.5		V
Analog Input:				
Input voltage (Recommended Operating Conditions), Range 1	0		+10	V
Input resistance, Range 1		120		kΩ
Input voltage (Recommended Operating Conditions), Range 2	0		+30	V
Input resistance, Range 2		147		kΩ
Output Supply Voltage 1-Wire:				
Supply voltage	+4.5		+4.7	V
Output inner resistance		7		Ω
Output current ($U_{out} > 3.0$ V)		30		mA

Short circuit current ($U_{out} = 0$)	75			mA
CAN Interface:				
Internal terminal resistors CAN bus	120			Ω
Differential input resistance	19	30	52	k Ω
Recessive output voltage	2	2.5	3	V
Differential input resistance	0.5	0.7	0.9	V
Common mode input voltage	-30		30	V
Power supply current (Hardware version with internal battery):				
Deep Sleep, average, $I_{cc.ds}$	2.5	4		mA
Sleep, average, $I_{cc.ds}$, $V_{cc}=10V$	45			mA
Sleep, average, $I_{cc.ds}$, $V_{cc}=30V$	25			mA
$U_{cc}=12.6V$, all modules fully working, internal battery is charging, I_{cc1}			350	mA
$U_{cc}=12.6V$, all modules fully working, internal battery is charging, I_{cc2}			300	mA
$U_{cc}=25.2V$, all modules fully working, internal battery is charging, I_{cc3}			195	mA
$U_{cc}=25.2V$, all modules fully working, internal battery is charging, I_{cc4}			140	mA

✘ Analog Input error margin can increase if temperature varies.