

# Template:FMM650 Electrical characteristics

## Electrical characteristics

<b>Characteristic description</b>	<b>Value</b>			<b>Unit</b>
	<b>Min.</b>	<b>Typ.</b>	<b>Max.</b>	
Supply Voltage:				
Supply Voltage (Recommended Operating Conditions)	+8		+32	V
Digital Output (Open Drain grade):				
Drain current (Digital Output OFF)			120	µA
Drain current (Digital Output ON, Recommended Operating Conditions)			0.5	A
Static Drain-Source resistance (Digital Output ON)	400	300		mΩ
Digital Input:				
Input resistance (DIN1)	15			kΩ
Input resistance (DIN2)	15			kΩ
Input resistance (DIN3)	15			kΩ
Input voltage (Recommended Operating Conditions)	0		Suppl y voltag e	V
Input Voltage threshold (DIN1)		7.5		V
Input Voltage threshold (DIN2, DIN3, DIN4)		2.5		V
Analog Input:				
Input voltage (Recommended Operating Conditions), Range 1	0		+10	V
Input resistance, Range 1		120		kΩ
Input voltage (Recommended Operating Conditions), Range 2	0		+30	V
Input resistance, Range 2		147		kΩ
Output Supply Voltage 1-Wire:				
Supply voltage	+3.3		+3.9	V
Output inner resistance	7			Ω
Output current ( $U_{out} > 3.0$ V)	30			mA
Short circuit current ( $U_{out} = 0$ )	75			mA
CAN Interface:				

Internal terminal resistors CAN bus	120/6 0		$\Omega$
Differential input resistance	19	30	$52\text{ k}\Omega$
Recessive output voltage	2	2.5	3 V
Differential input resistance	0.5	0.7	0.9 V
Common mode input voltage	-30	30	V
Power supply current (Hardware version with internal battery):			
Deep Sleep, average, $I_{cc.ds}$	2.5	4	mA
Sleep, average, $I_{cc.ds}$ , $V_{cc}=10V$	45		mA
Sleep, average, $I_{cc.ds}$ , $V_{cc}=30V$	25		mA
$V_{cc}=12.6V$ , all modules fully working, internal battery is charging, $I_{cc1}$		350	mA
$V_{cc}=12.6V$ , all modules fully working, internal battery is charging, $I_{cc2}$		300	mA
$V_{cc}=25.2V$ , all modules fully working, internal battery is charging, $I_{cc3}$		195	mA
$V_{cc}=25.2V$ , all modules fully working, internal battery is charging, $I_{cc4}$		140	mA
RS232/RS485 Input Voltage:			
RS232 input voltage range (common-mode voltage)	-15	+15	V
RS485 input voltage range on A or B pin (common-mode voltage)	-7	+12	V

Analog Input error margin can increase if temperature varies.

## Absolute maximum ratings

Characteristic description	Value		
	Min.	Typ.	Max.
Supply Voltage (Absolute Maximum Ratings)	-32		+32 V
Drain-Source clamp threshold voltage (Absolute Maximum Ratings), ( $I_{drain} = 2\text{ mA}$ )			+36 V
Digital Input Voltage (Absolute Maximum Ratings)	-32		+32 V
Analog Input Voltage (Absolute Maximum Ratings)	-32		+32 V
RS232 Input Voltage (Absolute Maximum Ratings)	-25		+25 V