

# Template:FMT1 First start card



Special and small waterproof GNSS tracker with built-in accelerometer.



## Contents

- [1 Know your device](#)
- [2 Pinout](#)
- [3 Set up your device](#)
  - [3.1 How to insert Micro-SIM card and connect the battery](#)

## Know your device



## Pinout

PIN NUMBER	PIN NAME	DESCRIPTION
1	<b>VCC</b> (10-30)V DC (+)	<b>(Red)</b> Power supply (+10-30 V DC)
2	<b>GND</b> (-)	<b>(Black)</b> Ground



## Set up your device

### How to insert Micro-SIM card and connect the battery

1. Unscrew **6 screws** counterclockwise.
2. Remove the **cover**.
3. Insert **Micro-SIM** card as shown with **PIN request disabled** or read [Security info](#) how to enter it later with [Teltonika Configurator](#). Make sure that Micro-SIM card **cut-off corner** is pointing forward to slot.
4. Connect the **battery** as shown to device. Position the battery in place where it does not

obstruct other components.

5. After **configuration**, see [PC Connection \(Windows\)](#), attach device **cover** back and **screw** in all screws.
6. Device is ready to be mounted.



**Micro-SIM card insertion/removal must be performed when device is powered off -**

-  **external voltage and battery are disconnected. Otherwise Micro-SIM card might be damaged or device will not detect it.**