

# Template:SAS device Parameter list - Beacon List

□

## Contents

- [1 Beacon List](#)
  - [1.1 Beacon Settings](#)
  - [1.2 Beacon List](#)
  - [1.3 Beacon On Demand](#)
  - [1.4 BLE Devices Settings](#)

## Beacon List

### Beacon Settings

Parameter ID	Parameter Type	Default value	Value range		Value	Parameter name
			Min	Max		
134	Uint16	0	0	3	0 - Disabled 1 - All 2 - Configured 3 - BLE Devices	Beacon Detection
136	Uint16	0	0	2	0 - Eventual 1 - Periodic 2 - No Send	Beacon Record

### Beacon List

Parameter ID	Default value	Beacons		Parameter name
		IBeacon	EddyStone	
1600-1699	""	UUID:Major:Minor Namespace:Instance ID		Beacon ID

### Beacon On Demand

Parameter ID	Parameter Type	Default value	Value range		Value	Parameter name
			Min	Max		
1750	Uint8	0	0	8	0 - Disable 8 - Button	Beacon On Demand
1751	Unit16	10	1	300	Seconds	Interval
1752	Unit16	3600	300	43200	Seconds	Duration

### BLE Devices Settings

Parameter ID	Parameter Type	Default value	Value range		Value	Parameter name
			Min	Max		
18000-18009	Uint8	0	0	0	0 - Disable 0 - Enable	Filter switch

<b>18050-18059</b>	Unit8	0	0	FF	Hexadecimal Value	Manufacturer ID
<b>18100-18109</b>	Unit8	0	0	32	Number	Manufacturer ID offset
<b>18150-18159</b>	Unit8	0	0	32	Number	Manufacturer ID size
<b>18200-18209</b>	Unit8	0	0	32	Number	Main data offset
<b>18250-18259</b>	Unit8	0	0	32	Number	Main data size
<b>18300-18309</b>	Unit8	0	0	32	Number	Additional data offset
<b>18350-18359</b>	Unit8	0	0	32	Number	Additional data size