

Template:SAS device Parameter list - Beacon List

□

Contents

- [1 Beacon List](#)
 - [1.1 Beacon Settings](#)
 - [1.2 Beacon List](#)
 - [1.3 Beacon On Demand](#)
 - [1.4 BLE Devices Settings](#)

Beacon List

Beacon Settings

Parameter ID	Parameter Type	Default value	Value range		Value	Parameter name
			Min	Max		
134	Uint16	0	0	3	0 - Disabled 1 - All 2 - Configured 3 - BLE Devices	Beacon Detection
136	Uint16	0	0	2	0 - Eventual 1 - Periodic 2 - No Send	Beacon Record

Beacon List

Parameter ID	Default value	Beacons		Parameter name
		IBeacon	EddyStone	
1600-1699	""	UUID:Major:Minor Namespace:Instance ID		Beacon ID

Beacon On Demand

Parameter ID	Parameter Type	Default value	Value range		Value	Parameter name
			Min	Max		
1750	Uint8	0	0	8	0 - Disable 8 - Button	Beacon On Demand
1751	Unit16	10	1	300	Seconds	Interval
1752	Unit16	3600	300	43200	Seconds	Duration

BLE Devices Settings

Parameter ID	Parameter Type	Default value	Value range		Value	Parameter name
			Min	Max		
18000-18009	Uint8	0	0	0	0 - Disable 0 - Enable	Filter switch

18050-18059	Unit8	0	0	FF	Hexadecimal Value	Manufacturer ID
18100-18109	Unit8	0	0	32	Number	Manufacturer ID offset
18150-18159	Unit8	0	0	32	Number	Manufacturer ID size
18200-18209	Unit8	0	0	32	Number	Main data offset
18250-18259	Unit8	0	0	32	Number	Main data size
18300-18309	Unit8	0	0	32	Number	Additional data offset
18350-18359	Unit8	0	0	32	Number	Additional data size