

[https://wiki.teltonika-gps.com/view/Wiki\\_test11](https://wiki.teltonika-gps.com/view/Wiki_test11)

# Wiki test11

{Scrolling table/top |first = top header 1

## SBD packet example

Unparsed data  
01004C01001CF99DD26333303032333430363430373038333000018000059282DBC03000B0036A2B8193D120000000302001C59282BA391F5ABCDBFDD018000059282BA891F5ABCDBFDD018000059282BA391F5AB

01004C01001CF99DD26333303032333430363430373038333000018000059282DBC03000B0036A2B8193D120000000302001C59282BA391F5ABCDBFDD018000059282BA891F5ABCDBFDD018000059282BA391F5AB

{01} - Protocol revision number {00}{4C} - overall message length {01} - MO header IEI  
{00}{1C} - MO header length {F9}{9D}{D2}{63} - CDR Reference  
{33}{30}{30}{32}{33}{34}{30}{36}{34}{30}{37}{30}{38}{33}{30}{30} - IMEI of the device {00}  
- Session status (Transfer OK in this case) {00}{18} - MOMSN {00}{00} - MTMSN  
{59}{28}{2D}{BC} - Time of session {03} - MO Location information IEI {00}{0B} - MO Location  
information length {00}{36}{A2}{B8}{19}{3D}{12} - MO latitude and longitude as described in  
Iridium documentation. {00}{00}{00}{03} - CEP radius {02} - Payload IEI {00}{1C} - Payload  
length {59}{28}{2B}{A3}{91}{F5}{AB}{CD}{BF}{DD}{01}{80}{00}{00} - Record 1  
{59}{28}{2B}{A8}{91}{F5}{AB}{CD}{BF}{DD}{01}{80}{00}{00} - Record 2 There blue part  
of record is satellite device generated data and green is actual record payload which was sent to  
server from FM63 device. Information of the first record should be parsed like this:  
{59}{28}{2B}{A3} - Timestamp of record generation in GMT0; {91}{F5}{AB} - Longitude  
(recalculated value is 25,255756) {CD}{BF}{DD} - Latitude (recalculated value is 54,832396) {01}  
- DIN1 generated event {80} - DIN1 on, while DIN2, DIN3, DIN4, DOUT1, DOUT2, DOUT3, DOUT4  
- off {00} - Reserved byte {00} - Vehicle was stopped then record is generated