

FMB640 J1708

[Main Page](#) > [EOL Products](#) > [FMB640](#) > [FMB640 Manual](#) > **FMB640 J1708**



Contents

- [1 Description](#)
- [2 Software Configuration of FMB640 with J1708](#)
- [3 Connection with Vehicle port](#)

Description

SAE J1708 is a standard used for serial communications between ECUs on heavy-duty. The hardware utilized is RS-485 transceivers wired for open collector operation through the use of a pullup and pulldown of the separate data lines.

With [FMB640](#), J1708 functionality is used to read vehicle's Fuel Level and Fuel consumption.

Because J1708 is not a CAN-BUS protocol, [FMB640](#) CAN1 and CAN2 lines cannot be used to read J1708 information. [FMB640](#) has a special J1708 Port, which utilizes an RJ9 4P4C connector.



Software Configuration of FMB640 with J1708

Firmware version: 00.00.11 or above

Configurator version: 0.13.35.29297 or above

J1708 configuration is done in the [FMS IO](#) Tab.

FMS Fuel Settings					
Fuel level source	Fuel consumption source		High resolution engine total fuel used		
CAN	J1708	CAN	J1708	Liters	Milliliters

When J1708 is enabled as a Fuel Level source, Fuel-related data will be taken from the J1708 line, FMS Fuel data will be ignored.

Connection with Vehicle port

J1708 connector is not supported by all vehicles. Only VOLVO, RENAULT, and American truck manufacturers implement the J1708 connector.

Trucks utilize *Deutsch 6-PIN or Deutsch 9-PIN connector*, which are used to connect FMB640 to J1708.



 **NOTE: Most of the Volvo trucks need an J1708 connection to be able to receive fuel level data**