

FMB900 General description

[Main Page](#) > [Basic Trackers](#) > [FMB900](#) > [FMB900 Manual](#) > **FMB900 General description**

FMB900 is a tracking terminal with GNSS and GSM connectivity, which is able to collect device coordinates and transfer them via GSM network to a server. This device is perfectly suitable for applications, which require the location acquirement of remote objects.



Contents

- [1 Package contents](#)
- [2 Basic characteristics](#)
- [3 Technical features](#)
- [4 Electrical characteristics](#)
- [5 Absolute maximum ratings](#)

Package contents

The FMB900 device is supplied to the customer in a cardboard box containing all the equipment that is necessary for operation. The package contains:

- Already implemented FMB900 device into case;
- Top and bottom device cover parts;
- and output power supply cable with a 1x5 connection pins, which is already installed into device.

Basic characteristics

GSM / GPRS / GNSS features:

- Teltonika [TM2500](#) quad band module (GSM 850 / 900 / 1800 / 1900 MHz);
- GPRS class 12 (Up to 85,6 kbps);
- SMS (text, data);
- Integrated GNSS receiver;
- Up to -165 dBm GNSS receiver sensitivity.

Hardware features:

- Built-in movement sensor;
- Built-in Bluetooth® 4.0;
- Internal High Gain GNSS antenna;
- Internal High Gain GSM antenna;
- 128 MB Flash (422 400 Records).

Interface features:

- Power supply: +6... +30 V;
- 1 digital input;
- 1 analog input;
- 1 open collector digital output (connecting external relays, LED, buzzers etc);
- 2 LEDs indicating device status.

Special features:

- Fast position fix (Outdoor areas);
- High Quality track even in high density urban canyon;
- Ultra small case;
- Ready for harsh environment;
- Easy to mount in limited access areas;
- Firmly fasten;
- 2 LED status indication;
- Real time tracking;
- Smart data acquisition based on:
 - Time;
 - Speed;
 - Angle;
 - Distance;
 - Ignition or any other I/O event;
- Sending acquired data via GPRS;
- GPRS and SMS I/O events;
- Virtual odometer;
- Jamming detection;
- Configurable using Secured SMS Commands;
- Color ribbon non-detachable cable;
- Overvoltage protection;

Description	Voltage	Duration
Normal operation	+6 ... +30 V	Unlimited
Protection turns on, device turns off	34 V	Unlimited
Maximum voltage	<70 V	Unlimited
Maximum voltage impulse	90 V	5ms

Technical features

Part name	Physical specification
Navigation indication	LED
Modem indication	LED

Socket	Soldered inner socket
USB	Micro USB socket

Technical details

2 W max. Current consumption at 12 V (Power supply 6...30 V DC)	GPRS: average 50 mA
	Nominal: average 35 mA
	GNSS sleep: average 5.58 mA
	Deep Sleep: average 4.06 mA
	Online Deep Sleep: average 4.62 mA
Operating temperature	Ultra Deep Sleep: average 2.08 mA
	Rated current: 250 mA
	-40 ... +85 °C
	-40 ... +85 °C
	5 ... 95% (no condensation)
Storage temperature	
Storage relative humidity	
Device + case weight	50 g

Dimension drawing:



Electrical characteristics

Characteristic description	Value		
	Min.	Typ.	Max. Unit
Supply Voltage:			
Supply Voltage (Recommended Operating Conditions)	6		30 V
Digital Output (Open Drain grade):			
Drain current (Digital Output OFF)			120 µA
Drain current (Digital Output ON, Recommended Operating Conditions)	0.1		0.5 A
Digital Input:			300 mΩ
Digital Output (Open Drain grade):			
Input resistance (DIN1)	47		kΩ
Input voltage (Recommended Operating Conditions)	0		Supply voltage V
Input Voltage threshold (DIN1)		4	V
Analog Input:			
Input voltage (Recommended Operating Conditions)	0		30 V
Input resistance		150	kΩ
Measurement error on 12 V		3	%

Additional error on 12 V	360	mV
Measurement error on 30 V	3	%
Additional error on 30 V	900	mV

 **Analog Input error margin can increase if temperature varies.**

Absolute maximum ratings

Characteristic description	Value		
	Min.	Typ.	Max. Unit
Supply Voltage (Absolute Maximum Ratings)	-32		+32 V
Drain-Source clamp threshold voltage (Absolute Maximum Ratings), ($I_{\text{drain}} = 2 \text{ mA}$)			+36 V
Digital Input Voltage (Absolute Maximum Ratings)	-32		+32 V
Analog Input Voltage (Absolute Maximum Ratings)	-32		+32 V