

# FMC225 General description

[Main Page](#) > [Professional Trackers](#) > [FMC225](#) > [FMC225 Manual](#) > **FMC225 General description**

FMC225 is a tracking terminal with GNSS and GSM connectivity, which is able to collect device coordinates and transfer them via GSM network to a server. This device is perfectly suitable for applications, which require the location acquirement of remote objects.



## Contents

- [1 Package contents](#)
- [2 Basic characteristics](#)
- [3 Technical features](#)
- [4 Technical information about internal battery](#)
- [5 Electrical characteristics](#)
- [6 Absolute maximum ratings](#)

## Package contents

The FMC225 device is supplied to the customer in a cardboard box containing all the equipment that is necessary for operation. The package contains:

- FMC225 device;
- Input and output power supply cable with 2x6 connection pins;
- Micro USB cable;
- 3.7 V 170 mAh rechargeable Li-ion battery;

## Basic characteristics

GSM / GPRS / GNSS features:

- Name MeiG SLM320-E, MeiG SLM320-LA, Quectel EC21-EC, Quectel EC21-AU, Quectel EC21-J, Quectel EC21-KL, Teltonika TM2500;
- Technology LTE(CaT1)/3G(UMTS/HSPA)/2G(GSM/GPRS)/GNSS(BLUETOOTH);
- SMS (text, data);
- Integrated GNSS receiver;
- Up to -165 dBm GNSS receiver sensitivity.

CELLULAR:

Technology	Supported bands
2G bands	FMC225-MBIB0: GSM: B2/B3/B5/B8
	FMC225-MCIB0: GSM: B2/B3/B5/B8

4G bands (SLM320)	FMC225-MBIB0: LTE FDD: B1/B3/B7/B8/B20/B28 LTE-TDD:B38/B40/B41
	FMC225-MCIB0: LTE FDD: B1/B2/B3/B4/B5/B7/B8/B20/B28 LTE-TDD:B40
Data transfer	LTE: LTE FDD: Max 10Mbps (DL)/Max 5Mbps (UL)
	LTE TDD: Max 8Mbps (DL)/Max 2Mbps (UL)
	GSM: GPRS: Max 85.6Kbps (DL)/Max 85.6Kbps (UL)

Transmit power:

Class 4 for GSM850/900:  $23\pm 2\text{dBm}$

Class 1 for GSM1800/1900:  $20\pm 2\text{dBm}$

Class 3 for LTE-TDD:  $23\pm 2.7\text{dBm}$

Class 3 for LTE-FDD:  $23\pm 2.7\text{dBm}$

Hardware features:

- Built-in movement sensor;
- Built-in Bluetooth 4.0 LE;
- Internal High Gain GNSS antenna;
- Internal High Gain GSM antenna;
- Internal flash memory 128MB (422 400 Records);
- 170 mAh Li-ion rechargeable 3.7 V battery.

Interface features:

- Power supply: +10... +30 V;
- 2 digital inputs;
- 1 analog input;
- 1 open collector digital output (connecting external relays, LED, buzzers etc);
- 1-Wire temperature sensor;
- 1-Wire iButton;
- LVCAN RX (INPUT 5);
- LVCAN TX (INPUT 6);
- 1 RS-232 interface;
- 1 RS-485 interface;
- 2 LEDs indicating device status.

Special features:

- Fast position fix (Outdoor areas);
- High Quality track even in high density urban canyon;
- Ultra small case;
- Ready for harsh environment;
- Easy to mount in limited access areas;
- Firmly fasten;

- 2 LED status indication;
- Real time tracking;
- Smart data acquisition based on:
  - Time;
  - Speed;
  - Angle;
  - Distance;
  - Ignition or any other I/O event;
- Sending acquired data via GPRS;
- GPRS and SMS I/O events;
- Virtual odometer;
- Jamming detection;
- Configurable using Secured SMS Commands;
- 1x micro SIM card; 1x eSIM;
- Overvoltage protection;

Description	Voltage	Duration
Normal operation	+10 ... +30 V	Unlimited
Protection turns on, device turns off	34 V	Unlimited
Maximum voltage	< 70 V	Unlimited
Maximum voltage impulse	90 V	5 ms

## Technical features

Part name	Physical specification
Navigation indication	LED
Modem indication	LED
Socket	Soldered inner socket
USB	Micro USB socket
GNSS	Internal GNSS antenna
GSM	Internal GSM antenna

### Technical details

	GPRS: average 64.59 mA rms
	Nominal: average 37.77 rms
2 W max. Current consumption at 12 V (Power supply 6...30 V DC)	GNSS sleep: average 11.1 mA Deep Sleep: average 6.2 mA Online Deep Sleep: average 6.5 mA
Battery charge current	Average 140 mA
Operating temperature (without battery)	-20..+85 °C
Storage temperature (without battery)	-20..+85 °C
Storage relative humidity	5..95% (no condensation)
Device + case + battery weight	52 g
Ingress Protection Rating	IP67

Dimension drawing:




## Technical information about internal battery

Internal back-up battery	Battery voltage (V)	Nominal Capacity (mAh)	Power (Wh)	Charge temperature (°C)	Discharge temperature (°C)	Storage temperature (°C)
Li-ion rechargeable battery	3.75□3.90	170	0.64 - 0.66	0 to +45	-20 to +60	-20 to +45 for 1 month -20 to +35 for 6 months

Batteries are covered by 6 month [warranty](#) support.

-  CAUTION: RISK OF EXPLOSION IF BATTERY IS REPLACED BY AN INCORRECT TYPE.  
DISPOSE OF USED BATTERIES ACCORDING TO THE INSTRUCTIONS.

Battery should not be disposed of into general household waste.

-  Bring damaged or worn-out batteries to your local recycling center or dispose them into a battery recycle bin commonly found in supermarkets.

## Electrical characteristics

Characteristic description	Value		
	Min.	Typ.	Max. Unit
Supply Voltage:			
Supply Voltage (Recommended Operating Conditions)	+10	+30	V

**Digital Output (Open Drain grade):**

Drain current (Digital Output OFF)	120	μA
------------------------------------	-----	----

**Drain current**

(Digital Output ON, Recommended Operating Conditions)	0.1	0.5	A
---	-----	-----	---

**Static Drain-Source resistance  
(Digital Output ON)**

400	600	mΩ
-----	-----	----

**Digital Input:**

Input resistance (DIN1)	47	kΩ
-------------------------	----	----

Input resistance (DIN2)	51.7	kΩ
-------------------------	------	----

Input voltage (Recommended Operating Conditions)	0	Supply voltage	V
---	---	-------------------	---

Input Voltage threshold (DIN1)	7.5	V
--------------------------------	-----	---

Input Voltage threshold (DIN2)	2.5	V
--------------------------------	-----	---

**Analog Input:**

Input voltage (Recommended Operating Conditions), Range 1	0	+10	V
--	---	-----	---

Input resistance, Range 1	150	kΩ
---------------------------	-----	----

Measurement error on 12V, Range 1	3	%
-----------------------------------	---	---

Additional error on 12 V, Range 1	360	mV
-----------------------------------	-----	----

Measurement error on 30 V, Range 1	3	%
------------------------------------	---	---

Additional error on 30 V, Range 1	900	mV
-----------------------------------	-----	----

Input Voltage (Recommended Operating Conditions), Range 2	0	+30	V
--	---	-----	---

Input resistance, Range 2	150	kΩ
---------------------------	-----	----

Measurement error on 12V, Range 2	3	%
-----------------------------------	---	---

Additional error on 12 V, Range 2	360	mV
-----------------------------------	-----	----

Measurement error on 30 V, Range 2	3	%
------------------------------------	---	---

Additional error on 30 V, Range 2	900	mV
-----------------------------------	-----	----

**Output Supply Voltage 1-Wire:**

Supply voltage	+4.5	+4.7	V
----------------	------	------	---

Output inner resistance	7	Ω
-------------------------	---	---

Output current ( $U_{out} > 3.0$ V)	30	mA
-------------------------------------	----	----

Short circuit current ( $U_{out} = 0$ )	75	mA
---	----	----

 **Analog Input error margin can increase if temperature varies.**

**Absolute maximum ratings**

Characteristic description	Value		
	Min.	Typ.	Max. Unit

Supply Voltage (Absolute Maximum Ratings)	-32	+32 V
Drain-Source clamp threshold voltage (Absolute Maximum Ratings), ( $I_{\text{drain}} = 2 \text{ mA}$ )		+36 V
Digital Input Voltage (Absolute Maximum Ratings)	-32	+32 V
Analog Input Voltage (Absolute Maximum Ratings)	-32	+32 V