

FMM130 SMS events

[Main Page](#) > [Advanced Trackers](#) > [FMM130](#) > [FMM130 Configuration](#) > **FMM130 SMS events**

SMS events functionality allows FMM130 to send a configured SMS when an event is triggered. This event can be triggered by every I/O element.

When any of the I/O elements is triggered, FMM130 sends a configured SMS message to a defined phone number. If SMS events are activated but there are no numbers defined in *GSM Predefined Numbers* list (similarly as in the picture below), then the device will not send any messages.



The sent SMS messages format is following:

"Date Time Current Coordinate Event Text"

For example, if FMM130 is configured to send an SMS, when Ignition reaches high level while configured with *High priority* and event generation on both range entrance and exit (as shown on the figure below), then the sent SMS is:

"2017/06/13 13:52:18 Lon:25.255537 Lat:54.667193 Ignition 1"

The screenshot shows the FMM130 configuration interface. At the top, there are buttons for 'Load from device', 'Save to device', 'Update firmware', 'Reset configuration', 'Load from file', 'Save to file', 'Read records', and 'Reboot device'. On the right, there is a 'FMM130' logo and device information: IMEI 352000000000000, FW 01.00.00 Rev:00, and Configuration 1.00.0.0. A left sidebar contains a menu with categories like Status, Security, System, GPRS, Data Acquisition, SMS \ Call Settings, GSM Operators, Features, Accelerometer Features, Auto Geofence, Manual Geofence, Trip \ Odometer, Bluetooth, Bluetooth 4.0, 1-Wire, I/O (highlighted), OBD II, and CAN Adapter. The main area displays an 'I/O' table with columns for Input Name, Units, Priority, Low Level, High Level, Event Only, Operand, Avg Const, Send SMS To, and SMS Text. The 'Priority' column has sub-columns for None, Low, High, and Panic. The 'Event Only' column has sub-columns for Crash, Yes, and No. The 'Send SMS To' column has a dropdown menu. The 'SMS Text' column contains the text for each event.

Input Name	Units	Priority				Low Level	High Level	Event Only			Operand	Avg Const	Send SMS To	SMS Text
		None	Low	High	Panic			Crash	Yes	No				
Ignition		None	Low	High	Panic	0	0	Crash	Yes	No	On Change	10		Ignition
Movement		None	Low	High	Panic	0	0	Crash	Yes	No	On Change	10		Movement
Data Mode		None	Low	High	Panic	0	0	Crash	Yes	No	Monitoring			Data Mode
GSM Signal		None	Low	High	Panic	0	0	Crash	Yes	No	Monitoring	1		GSM Signal
Sleep Mode		None	Low	High	Panic	0	0	Crash	Yes	No	Monitoring			Sleep Mode
GNSS Status		None	Low	High	Panic	0	0	Crash	Yes	No	Monitoring			GNSS Power
GNSS PDOP		None	Low	High	Panic	0	0	Crash	Yes	No	Monitoring	10		GNSS PDOP
GNSS HDOP		None	Low	High	Panic	0	0	Crash	Yes	No	Monitoring	10		GNSS HDOP
External Voltage	mV	None	Low	High	Panic	0	0	Crash	Yes	No	Monitoring	10		External Voltage
Speed	km/h	None	Low	High	Panic	0	0	Crash	Yes	No	Monitoring	1		Speed
GSM Cell ID		None	Low	High	Panic	0	0	Crash	Yes	No	Monitoring			GSM Cell ID
GSM Area Code		None	Low	High	Panic	0	0	Crash	Yes	No	Monitoring			GSM Area Code
Battery Voltage	mV	None	Low	High	Panic	0	0	Crash	Yes	No	Monitoring	10		Battery Voltage
Battery Current	mA	None	Low	High	Panic	0	0	Crash	Yes	No	Monitoring	10		Battery Current
Active GSM Operator		None	Low	High	Panic	0	0	Crash	Yes	No	Monitoring			Active GSM Operator
Trip Odometer	m	None	Low	High	Panic	0	0	Crash	Yes	No	Monitoring			Trip Odometer
Total Odometer	m	None	Low	High	Panic	0	0	Crash	Yes	No	Monitoring			Total Odometer
Digital Input 1		None	Low	High	Panic	0	0	Crash	Yes	No	Monitoring	1		Dig. Input 1
Analog Input 1	mV	None	Low	High	Panic	0	0	Crash	Yes	No	Monitoring	10		Analog Input 1
Digital Output 1		None	Low	High	Panic	0	0	Crash	Yes	No	Monitoring	10		Dig. Output 1
Digital Output 3		None	Low	High	Panic	0	0	Crash	Yes	No	Monitoring	10		Dig. Output 1
Fuel Used GPS	ml	None	Low	High	Panic	0	0	Crash	Yes	No	Monitoring	1		FC By GNSS
Fuel Rate GPS	l/h*100	None	Low	High	Panic	0	0	Crash	Yes	No	Monitoring	1		FC AVG By GNSS
Axis X	mG	None	Low	High	Panic	0	0	Crash	Yes	No	Monitoring	1		Axis X
Axis Y	mG	None	Low	High	Panic	-4	0	Crash	Yes	No	Monitoring	1		Axis Y
Axis Z	mG	None	Low	High	Panic	0	0	Crash	Yes	No	Monitoring	1		Axis Z
ICCID		None	Low	High	Panic			Crash	Yes	No	Monitoring			ICCID Value
Ground Sense		None	Low	High	Panic	0	0	Crash	Yes	No	Monitoring	10		Grid. Sense
Digital Input 2		None	Low	High	Panic	0	0	Crash	Yes	No	Monitoring	1		Dig. Input 2

The SMS Text field can be altered and any text can be entered. Maximum message length is 160 symbols (numbers, letters and symbols in ASCII, except for comma symbol ",").



If FMM130 is in *Deep Sleep* mode and an SMS event occurs with *Low priority* (which does not wake up FMM130), then the device does not send the message. It is saved to device memory until it wakes up from *Deep Sleep* mode and GSM modem starts working normally. After it wakes up, all the messages that are saved to memory will be sent, but keep in mind that only 10 messages can be saved to memory - all other messages will not be saved, until there is free memory space.