

MINI-CAN

[Main Page](#) > [EOL Products](#) > **MINI-CAN**



MINI-CAN is contactless adapter used to read vehicle [CAN Bus](#) data. **MINI-CAN** adapter should be used in combination with:

- [LV-CAN200](#)
- [ALL-CAN300](#)
- [FMB140](#)
- [FMB640](#), [FMB630](#), [FM6320](#), [FM6300](#) to read [J1939](#) CAN data.

It reads can-bus data through the isolation of wires without damaging them and forwards signals to the tracking device.



Contents

- [1 Features](#)
- [2 Technical features](#)
- [3 Nomenclature, classification codes](#)
- [4 Certifications & Approvals](#)
- [5 FAQ](#)
- [6 YouTube](#)
- [7 Promotional Material](#)
- [8 External Links](#)

Features

- MINI-CAN collects vehicle data from CAN bus without damaging the wires
- Powered from an on-board power source
- Reads the signals through the isolation of CAN bus wires
- Easy to install and operate

Technical features

PARAMETER	VALUE				Unit
	Minim um	Typica l	Typica l	Maxim um	
Supply Voltage					
Supply Voltage (Recommended Operating Conditions)	+9	+12	+24	+63,5	V
Current Consumption					

Working Mode	8,3	4,3	mA
Sleep Mode	1,6	0,91	mA
Operating Temperature			
Operating Temperature	-40	+85	°C

- Dimension: 41.6 x 18.9 x 12.5 mm
- Weight: 9,1 g
- CAN-BUS speeds from 33,33 to 500 kb/s
- Automatically sets CAN Low, CAN High polarity
- Automatically adjusts signal level and speed

Nomenclature, classification codes

- [MINI-CAN LITAR](#)

Certifications & Approvals

- [MINI-CAN REACH](#)

FAQ

- How to install MINI-CAN with [LV-CAN200/ALL-CAN300](#) using:
 - [FMB110](#)
 - [FMB120](#)
 - [FMB122](#)
 - [FMB125](#)
 - [FMB110](#)
 - [FMA120](#)
 - [FMB630](#)
 - [FMB640](#)
 - [FM6300](#)
 - [FM6320](#)
 - [FM36M1](#)
 - [FM3622](#)
 - [FM3612](#)

YouTube

[Teltonika CAN adapters Part 1: Introduction](#)

[Teltonika CAN adapters Part 2: Installation](#)

Promotional Material

[MINI-CAN Promotional Material](#)

External Links

<https://teltonika-gps.com/product/mini-can/>