

Teltonika DashCam

[Main Page](#) > [Video Solutions](#) > **Teltonika DashCam**

Teltonika DashCam solution is perfect for capturing videos or pictures of the events that might occur on the road, e.g. crash. Mounted on the vehicle front window, one camera are used, front, to record videos before and after the events, take photos periodically or by request and send all data to the server. **Also the possibility to connect two cameras, DSM and DashCam or DualCam, to one device, FMC650.** By utilizing the two RS232 ports on the FMC650, you can connect the DSM camera for driver status monitoring to one port and the DualCam or DashCam camera for road and cargo monitoring to the second port. [Configuration](#)

DashCam is connected to **FMB125, FMC125 and FMB225, FMC225 and FMC650** devices using the RS232 interface.



- [First Start](#)
- [Camera Manual](#)
- [DashCam Configuration](#)
- [Data image/video review](#)
- [DashCam Communication Protocol](#)
- [DashCam Data Sending Parameters ID](#)
- [DashCam SMS commands](#)
- [DashCam Certifications & Approvals](#)
- [DashCam Troubleshoot](#)
- [DashCam Firmware errata](#)
- [DashCam Product Change Notifications](#)
- [DashCam FAQ](#)
- [DashCam Integration on platfroms](#)
- [DashCam EAN](#)
- [DashCam Testing](#)
- [CloudView Platform](#)

Downloads

Manual & Documentation



[DashCam Datasheet \(EN\)](#) (Updated on: 2024-01-02)