https://wiki.teltonika-gps.com/view/Template:FMB6\_Technical\_features

## **Template:FMB6 Technical features**

## **Technical features**

| Part name             | Physical specification   |
|-----------------------|--------------------------|
| Navigation indication | LED                      |
| Modem<br>indication   | LED                      |
| Socket                | Soldered inner socket    |
| USB                   | Mini USB socket          |
| GNSS                  | External GNSS<br>antenna |
| GSM                   | External GSM<br>antenna  |

## **Technical details**

| 2 W max.<br>Current consumption at 12 V | GPRS: average avg mA<br>rms<br>Nominal: average avg<br>rms<br>GNSS sleep: average avg<br>mA<br>Deep Sleep: average avg<br>mA<br>Online Deep Sleep:<br>average avg mA |
|---|--|
| 2 W max.<br>Current consumption at 24 V | GPRS: average 35 mA<br>Nominal: average 20 mA<br>GNSS sleep: average<br>12,5 mA<br>Deep Sleep: average 3,8<br>mA<br>Online Deep Sleep:<br>average 1,3 mA             |
| Battery charge current                  | Average 55 mA  |
| Operating temperature (without battery) | -40+85   |
| Storage temperature (without battery)   | -40+85   |
| Storage relative humidity               | 595% (no condensation)   |
| Device + case + battery weight          | 197 g  |
|   |  |

Dimension drawing:

×